

XPS-1008-18P

16 port 10/100 PoE + 2 port 10/100/1000T Unmanaged Switch



- 16 Port 10/100 PoE
- 2 Port 10/100/1000BaseT
- 280 Watt PoE Budget
- Each Port Supports 802.3af/at
- 250mt Long Reach Mode
- Mechanical VLAN Mode
- Activity and PoE LEDs
- Internal Power Supply



Technical Specs.

Model No	XPS-1008-18P
Port Capacity	18 Port Unmanaged PoE Switch
Port Types	16port 10/100 PoE + 2 port 10/100/1000T Unmanaged

Performance

Switching Capacity	7.2 Gbps, wire speed, (non-blocking)
Forwarding Rate	5.35 Mpps
MAC Table	2K
Jumbo Frames	9K
Flash RAM	128M
RAM	512M
Auto-negotiation	✓
Auto MDI/MDIX	✓
Store-and-Forward	✓

PoE Features

Total PoE Budget	280 Watt
PoE Standarts	802.3af/at for all PoE ports
Max. Watt Per Port	30 Watt
PoE Distance	Normal Mode 100 mt. , Extend Mode 250mt.

Dip Switch

Normal Mode	100mt PoE distance
Extend Mode	250mt PoE distance
VLAN Mode	Mech. VLAN , 16 Port can only comm. with uplink ports

Environment

Input Power	Built-in power AC 100~240V 50/60HZ
Total Power Consumption	Max. 295 Watt
Operating/Storage Temperature	-5 - 50 °C / -40 - 75 °C
Operating Humidity	5% - 90%, non-condensing

Mechanical

Dimension	268 x 181 x 44 mm
Weight	1.28 kg
Installation	Free-standing

Standards

CE mark, commercial	FCC Part 15 Class B
VCCI Class B	ISO 9001
EN55022 (CISPR 22), Class B	CE/LVD EN60950, RoHS

Ordering Information

XPS-1008-18P	16 port 10/100 PoE + 2 port 10/100/1000T Unmanaged Switch
---------------------	---