

XPS-1100-26P

24 Port 10/100 PoE + 2 Gigabit Combo Unmanaged PoE Switch



- 24 Port 10/100 PoE
- 2 Gigabit Combo
- Total PoE Budget: 250W
- IEEE802.3x

Technical Specs.

Model No	XPS-1100-26P
Port Capacity	24 Port PoE + 2 Gigabit Combo Unmanaged PoE Switch
Port Types	24 port 10/100Base-TX RJ45 copper ports (PoE) + 2 Gigabit Combo (1000T/SFP)

Performance

Switching Capacity	8.8 Gbps (non-blocking)
Forwarding Rate	6.55 Mpps
MAC Table	4K

Features

IEEE 802.3	IEEE 802.3z	IEEE 802.3af
IEEE 802.3i	IEEE 802.3ab	IEEE 802.3at
IEEE 802.3u	IEEE 802.3x	Auto MDI/MDIX
Switch Architecture, Store-and-Forward		Auto Negotiation

PoE

Standard	IEEE802.3af IEEE 802.3at
Total PoE Budget	250W
Max. PoE Power for each port	30W

Environment

Input Power	AC100-240V 50-60Hz
Total Power Consumption	261W
Operating/Storage Temperature	0 - 50 °C / -20 - 75 °C
Operating Humidity	10% - 90%, non-condensing

Mechanical

Dimension	440 x 275 x 44.5 mm
Weight	4.878 kg
Installation	Free-standing, wall-mounted

Standards and Protocols

CE Mark, commercial	EN 55022 (CISPR 22), Class B
FCC Part 15 Class B	CE/LVD EN60950
VCCI Class B	ISO 9001

Ordering Information

XPS-1100-26P	24 Port 10/100 PoE + 2 Gigabit Combo Unmanaged PoE Switch (250 W)
---------------------	---

Modules

XPS-21LX	XPS Dual Core LX SM 10Km SFP Module -10/50°C
XPS-21SX	XPS Dual Core SX MM SFP Module -10/50°C

*more module ranges are available upon request.