

XPS-1200-8P

7 port 10/100/1000 PoE + 1 port 10/100/1000T Uplink Unmanaged Switch



- 7 Port 10/100/1000 PoE
- 1 Port 10/100/1000 Uplink
- Total PoE Budget: 130W
- IEEE802.3x

Technical Specs.

Model No	XPS-1200-8P
Port Capacity	8 Port Unmanaged PoE Switch
Port Types	7 port 10/100/1000Base-T RJ45 copper ports (PoE) + 1 port 10/100/1000 RJ45 copper port

Performance

Switching Capacity	16 Gbps, wire speed, (non-blocking)
Forwarding Rate	11.90 Mpps
MAC Table	8K

Features

IEEE 802.3	IEEE 802.3z	IEEE 802.3af
IEEE 802.3i	IEEE 802.3ab	IEEE 802.3at
IEEE 802.3u	IEEE 802.3x	Auto MDI/MDIX
Switch Architecture, Store-and-Forward		Auto Negotiation

PoE

Standard	IEEE802.3af IEEE 802.3at
Power Supply Type	End-span
Total PoE Budget	130 W
Max. PoE Power for each port	30 W

Environment

DC Power Input	47-55V
Total Power Consumption	141 W
Operating/Storage Temperature	0 - 50 °C / -20 - 75 °C
Operating Humidity	10% - 90%, non-condensing

Mechanical

Dimension	279 x 195 x 44 mm
Weight	1.466 kg
Installation	Free-standing, wall-mounted

Standards and Protocols

CE Marks, commercial	EN 55022 (CISPR 22), Class B
EN 55022 (CISPR 22), Class B	CE/LVD EN60950, RoHS
VCCI Class B	ISO 9001

Ordering Information

XPS-1200-8P	7 port 10/100/1000 PoE + 1 port 10/100/1000T Uplink Unmanaged Switch
--------------------	--